

SAFETY DATA SHEET ACCORDING TO REGULATION (EC) 1907/2006

EURO-LOCK[®]
Chemisch-Technische-Produkte

Product name: Locomotive cleaner, 500 ml - 6856

Creation date: 11.10.2021, Revision: 21.08.2023, version: 3.4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name

Locomotive cleaner, 500 ml - 6856

Article

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Cleaning agent.

Uses advised against

No information.

1.3 Details of the supplier of the safety data sheet

Supplier

EURO-LOCK Vertriebs GmbH
Nordweststr. 3
59387 Ascheberg, Germany
+49 (0)2593 / 95887-0
info@euroloc.de
www.euro-lock.de

HG's Modellbahnambulanz
Stäffelsbergstr. 7
76889 Dörrenbach, Germany
+49 (0)6343 / 9249822
info@modellbahnambulanz.de
www.modellbahnambulanz.de

Viessmann Modelltechnik GmbH
Bahnhofstraße 2a
35116 Hatzfeld-Reddighausen
+49 (0)6452 / 96400
info@viessmann-modell.com
www.viessmann-modell.com

1.4 Emergency Telephone Number Emergency

112

Supplier

+49 (0)2593 / 95887-0

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315 Causes skin irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: DANGER**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P301 + P310 + P331 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.

P302 + P352 + P362 + P364 IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with local/national regulation.

Contains:

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

PBT/vPvB

No information.

Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

Additional information

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

For mixtures see 3.2.

3.2 Mixtures

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Concentration Limits	Notes for substances
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0 927-510-4 - 01-2119475515-33	50-100	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	/	/
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27	2,5-10	Flam. Gas 1; H220 Press. Gas; H280	/	C, U
carbon dioxide	124-38-9 204-696-9 -	2,5-10	Press. Gas; H280	/	/

propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	2,5-10	Flam. Gas 1; H220 Press. Gas; H280	/	U
n-hexane	110-54-3 203-777-6 601-037-00-0	<2,5	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Repr. 2; H361f STOT RE 2; H373 Aquatic Chronic 2; H411	STOT RE 2; H373; C ≥ 5%	/

Notes for substances

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product description

Hydrocarbons with a propellant.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Keep at rest in a position comfortable for breathing. If symptoms develop and persist, seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Seek medical help immediately. In case of unconsciousness bring patient into stable side position and seek medical attention.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Not likely. Accidental ingestion: Rinse mouth thoroughly with water. Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Vapours may cause drowsiness and dizziness. Excessive exposure to spray mist, fog, or vapours may cause respiratory

irritation. Coughing, sneezing, nasal discharge, labored breathing.

Following skin contact

Irritating to the skin. Itching, redness, pain.

Following eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Following ingestion

Not likely. Accidental ingestion: May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area. May be fatal if swallowed and enters airways.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Foam.

Fire extinguishing powder.

Carbon dioxide (CO₂).

Water spray. Extinguish large fires with water spray or alcohol-resistant foam.

Unsuitable extinguishing media

Full water jet. Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂). Various hydrocarbons.

Aldehydes. Soot.

5.3 Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Vapours can form explosive mixtures with air. Prolonged heating can cause an explosion. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Cool containers at risk with water spray. If possible remove containers from endangered area. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated extinguishing agents must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

Emergency procedures

Evacuate the danger zone. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Avoid contact with skin, eyes and clothing. Do not breathe vapour or mist.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Prevent release into the sewer, water, basements or confined areas. Collect the spray cans and hand them over to an authorized waste disposal contractor. Release of liquid because of damaged aerosol can (release of large quantities): In case of bigger spill, dam the spillage, pump the liquid into appropriate labelled containers, absorb the residue with absorbent material and dispose of according to local regulations. Do not absorb spillage with sawdust or other combustible material. Dispose in accordance with applicable regulations (see Section 13).

Other information

No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Protect from open fire and other sources of ignition or heat. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Vapours and air form explosive mixtures. Take precautionary measures against static discharges. Use spark-proof tools.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Avoid release to the environment.

Other measures

No information.

Advice on general occupational hygiene

Refer to instructions on label and regulations for safety and health at work. Consider measures required in Section 8 of this safety data sheet. Use personal protective equipment. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Store in accordance with local regulations. Keep in cool and well ventilated area. Keep in well closed containers. Keep away from sources of ignition - no smoking. Protect against heat and direct sunlight. Keep away from oxidising

substances. Keep away from food, drink and animal feeding stuffs.

Packaging materials

No information.

Requirements for storage rooms and vessels

Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions

No information.

7.3 Specific end use(s)

Recommendations

No information.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

Name	mg/m ³	ml/m ³	Short-term value mg/m ³	Short-term value ml/m ³	Remark	Biological Tolerance Values
Cycloalkanes ≥C7	800	/	/	/	/	/
Normal and branched chain alkanes ≥C7	1200	/	/	/	/	/
n-Hexane (110-54-3)	72	20	/	/	/	/
Carbon dioxide (124-38-9)	9150	5000	27400	15000	/	/

Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values

For product

No information.

For components

Name	Type	Exposure route	exp. frequency	Remark	value
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Worker	inhalation	long term systemic effects	/	2085 mg/m ³
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Worker	dermal	long term systemic effects	/	300 mg/kg bw/day
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Consumer	inhalation	long term systemic effects	/	447 mg/m ³
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Consumer	dermal	long term systemic effects	/	149 mg/kg bw/day
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Consumer	oral	long term systemic effects	/	149 mg/kg bw/day

PNEC values

For product

No information.

For components

No information.

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Keep away from foodstuffs, beverages and feed. If technical measures to reduce workers' exposure are not sufficient, and the limit values of hazardous substances in the air are exceeded, it is necessary to use personal protective equipment.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN ISO 16321-1:2022).

Hand protection

Protective gloves (BS EN ISO 374). The product consists of various substances, therefore the resistance of gloves can not be calculated and has to be tested before use.

Appropriate materials

Skin protection

Cotton protective clothing and shoes that cover the entire foot (BS EN ISO 20345:2022). Protective antistatic clothing BS EN 1149 (1:2006, 2:1997 and 3:2004, 5:2018), protective antistatic shoes (BS EN ISO 20345:2022). Choose body protection according to the activity and possible exposure.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Wear suitable protective breathing mask (BS EN 136) with filter A2-P2 (BS EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard BS EN 137, BS EN 138.

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid - aerosol

Colour

colourless

Odour

characteristic

Important health, safety and environmental information

Odour threshold	No information.
Melting point/Freezing point	No information.
Boiling point or initial boiling point and boiling range	No information.
Flammability	No information.
Lower and upper explosion limit	1.5 — 10.9 vol % (propellant)
Flash point	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
pH	substance/mixture is non-soluble (in water)
Viscosity	No information.
Solubility	No information.
Partition coefficient	No information.
Vapour pressure	< 70 hPa at 20 °C
Density and/or relative density	Density: 0.704 kg/L at 20 °C (data refers to the liquid portion of the product)
Relative vapour density	No information.
Particle characteristics	No information.

9.2 Other information

Weight organic solvents	678 g/l (VOC) 97 % (VOC)
Explosive properties	No information.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under recommended transport or storage conditions.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not expose to heat and direct sunlight. Do not store above 50°C.

10.5 Incompatible materials

Oxidants.
Strong acids.

10.6 Hazardous decomposition products

In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) Acute toxicity

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	dermal	LD ₅₀	rat	24 h	> 2920 mg/kg bw	/	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	oral	LD ₅₀	rat	/	> 5840 mg/kg bw	/	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	inhalation (vapours)	LC ₅₀	rat	4 h	> 23300 mg/m ³	OECD 403	/

Additional information

The product is not classified as acutely toxic.

(b) Skin corrosion/irritation

For components

Name	Species	Time	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	/	/	Irritating.	/	/

Additional information

Causes skin irritation.

(c) Serious eye damage/irritation

For components

Name	Exposure route	Species	Time	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	/	/	/	Not classified.	/	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	/	/	/	Contact with eyes may cause irritation.	/	/

Additional information

The product is not classified as an irritant to the eyes.

(d) Respiratory or skin sensitisation

For components

Name	Exposure route	Species	Time	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	/	/	Not classified.	/	/

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

For components

Name	Type	Species	Time	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Genotoxicity	/	/	Negative.	/	/

(f) Carcinogenicity

For components

Name	Exposure route	Type	Species	Time	value	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	/	/	/	/	/	Substance is not classified as carcinogenic.	/	/

(g) Reproductive toxicity

For components

Name	Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Reproductive toxicity	/	rat	/	/	The results of animal studies gave no indication of a fertility impairing effect.	/	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Developmental toxicity	/	rat	/	/	Did not show teratogenic effects in animal experiments.	/	/
n-hexane	Reproductive toxicity	/	/	/	/	Suspected of damaging fertility.	/	/

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

For components

Name	Exposure route	Type	Species	Time	Exposure	organ	value	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	inhalation	-	/	/	/	/	/	May cause effects on the central nervous system.	/	high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	inhalation	-	/	/	/	/	/	Symptoms: nausea, unconsciousness.	/	high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	inhalation	-	/	/	/	/	/	Symptoms: mucous membrane irritation.	/	high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	inhalation	-	/	/	/	/	/	May cause respiratory irritation.	/	high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	oral	-	/	/	/	/	/	May cause irritation of the digestive tract.	/	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	-	/	/	/	/	/	May cause drowsiness or dizziness.	/	/
carbon dioxide	inhalation	-	human	/	/	/	/	1 % CO ₂ in the air: slight increase in breathing rate.	/	/

carbon dioxide	inhalation	-	human	/	/	/	/	2 % CO2 in the air: a 50 % increase in breathing rate.	/	/
carbon dioxide	inhalation	-	human	/	/	/	/	3 % CO2 in the air: a two-times increase in breathing rate, decreased hearing, headache, slight narcotic effect, increased blood pressure and pulse.	/	/
carbon dioxide	inhalation	-	human	/	/	/	/	4-5% concentration of CO2 in the air: an increase in breathing rate by four times, symptoms of intoxication become noticeable, a choking feeling.	/	/
carbon dioxide	inhalation	-	human	/	/	/	/	5-10 % CO2 in the air: headache, tinnitus and dizziness; after a few minutes - loss of consciousness.	/	/
carbon dioxide	inhalation	-	human	/	/	/	/	10-100 % CO2 in the air: unconsciousness occurs rapidly at concentrations above 10%; it can be harmful or fatal.	/	/

Additional information

May cause drowsiness or dizziness.

(i) STOT-repeated exposure

No information.

Additional information

STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

For components

Name	result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Aspiration into the lungs can cause lung damage.	/	The exposed person should be kept under medical surveillance for 48 hours.
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	May be fatal if swallowed and enters airways.	/	/

Additional information

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

No information.

Interactive effects

No information.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

Other information

No information.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	ErL ₅₀	10 - 30 mg/L	72 h	algae	<i>Pseudokirchneriel la subcapitata</i>	OECD 201	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EbL ₅₀	10 - 30 mg/L	72 h	algae	<i>Pseudokirchneriel la subcapitata</i>	OECD 201	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EL ₅₀	3 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LL ₅₀	> 13.4 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	OECD 203	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	NOELR	6.3 mg/L	72 h	algae	<i>Pseudokirchneriel la subcapitata</i>	OECD 201 OECD 201	/

Chronic (long-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	NOELR	1 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	/
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	NOELR	1.53 mg/l	28 days	fish	<i>Oncorhynchus mykiss</i>	QSAR Petrotox QSAR Petrotox	/

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

Name	Type	Rate	Time	Evaluation	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	biodegradability	98 %	28 days	readily biodegradable	OECD 301 F	/

12.3 Bioaccumulative potential

Partition coefficient

No information.

Bioconcentration factor (BCF)

No information.

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 Results of PBT and vPvB assessment

No evaluation.

12.6 Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

12.7 Other adverse effects

No information.

12.8 Additional information

For product

Toxic to aquatic life with long lasting effects. Water hazard class (WGK): 3 (Self-assessment), very hazardous for water. Do not allow to reach ground water, water courses or sewage system.

For components

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

carbon dioxide

When discharged in large quantities may contribute to the greenhouse effect (GWP=1).

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Avoid release to the environment. Dispose of in accordance with applicable waste disposal regulation. Disposal must be

made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Product and container must be disposed of safely.

Waste codes / waste designations according to LoW

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

Packaging

Uncleaned containers should not be perforated, cut or welded. Pressurized container. Do not pierce or burn, even after use. Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW

15 01 11* - metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

Waste treatment-relevant information

No information.

Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2 UN proper shipping name			
AEROSOLS	AEROSOLS (hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	AEROSOLS	AEROSOLS
14.3 Transport hazard class(es)			
2	2	2	2
14.4 Packing group			
Not given/not applicable	Not given/not applicable	Not given/not applicable	Not given/not applicable
14.5 Environmental hazards			
YES	Marine pollutant	YES	YES
14.6 Special precautions for user			

Limited quantities 1 L Special provisions 190, 327, 344, 625 Packing Instructions P207, LP200 Special packing provisions PP87, RR6, L2 Transport category 2 Tunnel restriction code (D) Classification code 5F	Limited quantities 1 L EmS F-D, S-U	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y203 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 30 kg G Packing Instructions (Pkg Inst) 203 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 kg Special provisions A145, A167, A802	Limited quantities 1 L
14.7 Maritime transport in bulk according to IMO instruments			
	Goods may not be carried in bulk in bulk containers, containers or vehicles.		

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2020/878)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)
not applicable

Ingredients according to Regulation (EC) No 648/2004 on detergents
> 30%: aliphatic hydrocarbons

Special instructions

- Seveso III, P3a: flammable aerosols. Seveso III, E2: hazardous to the aquatic environment.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes

2.2 Label elements 2.3 Other hazards 6.3 Methods and material for containment and cleaning up 9.2 Other information
11.2 Information on other hazards 12.6 Endocrine disrupting properties

Key literature references and sources for data

No information.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment

CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.